

4 ATM LCD

10.4" Displays

Overview



- **Integrated resistive touch screen**
- **Ideal for installation in new ATMs, Kiosks and Self Service Equipments**

Features

| | |
|------------------------------------|---|
| Size | 10.4" |
| Active area | 211.2 x 158.4 mm |
| Pixel format | 800 x 600 x 3 |
| Display mode | Normally white |
| Brightness | 400 cd/m2 typ. (without touch) |
| Contrast | 700:1 typ |
| Brightness uniformity | 75% |
| Video Input Signal | DVI-D |
| Video Connector | 24 way DVI female |
| Touch screen | Resistive 5 wire |
| Touch screen connector | USB B connector (Molex 67068) |
| Supported Video Input Signal Modes | 640 x 480 - 800 x 600 - 1024 x 768 |
| Power Input | 24 Vdc; 0.6 A max |
| Power consumption | 24 W max |
| Power Connector | Molex connector (39-30-3035) |
| Approvals & Certifications | EN60950-1 UL60950-1 CSA C22.2 n. 60950-1 FCC CFR47 P.15 EN61000-6-3:2001 (Emissions) EN61000-4-2 (Electrostatic Discharge) EN61000-4-3 (RFI Radiated Susceptibility) EN61000-4-4 (Electrical Fast Transient) EN61000-4-6 (RFI Conducted Susceptibility) CE |
| Operating Temperature | 0 to +50° C |
| Storage Temperature | -10 to + 50° C |
| Backlight life | 50,000 hours typ |

4 ATM LCD

10.4" Displays

Cross References



| Original P/N | | Compatible P/N |
|---------------|------------|----------------|
| Equivalent to | | |
| 445-0683552 | G1000002 | G1000055 |
| 445-0697352 | G1000012 | |
| 445-0697353 | G1000014 | |
| 009-0024829 | G1000028 | |
| 009-0025942 | G1000041 | |
| 009-0026111 | G1000042MP | |
| 009-0026111 | G1000047MP | |
| 009-0026111 | G1000051MP | |

Additional solutions available upon request.



Global Display Solutions - www.gds.com

GDS Europe
T. +39 0445 428991
E. emea@gds.com

GDS America
T. +1 815 282 2328
F. +1 815 282 0297
E. america@gds.com

GDS Asia
T. +886 2 2298-1480
F. +886 2 2298-1131
E. asiapacific@gds.com